



INSTALED

Edifici Torre Mil-lenium
Avda. Francesc Macià, 60, 4t 2a
08208 – SABADELL BCN

T 937 246 871
F 937 161 127
www.instaled.es

(140W LED CAMPANA IND.)

Voltaje entrada	AC90-265V	
Rango frecuencia	50Hz-60Hz	
Total distorsión armónica	<=9%	
Factor potencia	>0.95	
Potencia eficaz	>92	
LED	BRIDGELUX	
Consumo LED	140W	
Eficacia luminosa LED	100-110Lm/W	
Flujo inicial LED	WW	>13.200lm
	NW	>14.200lm
	CW	>14.500lm
Eficiencia lámpara	>85%	
Uniformidad luminaria	>0.4	
Temperatura color	WW	2700K-3200K
	NW	4000K-5000K
	CW	5500K-6000K
Índice de reproducción	WW	Ra>68
	NW,CW	Ra>75
Angulo haz	45/90/120°	
Temperatura unión	<=85°C	
Temperatura trabajo	-40°C + 55°C	
Driver incluido	Mean Well	
Vida LED	>40000 Hr	
Sección línea	1.5 mm2 x3	
Cables conexión	Marrón	L
	Azul	N
	Amarillo	G
Peso luminaria	8.5 Kg	
Grado protección	IP 65	
Reflector aluminio		

